



STANDARD BALL VALVE – SINGLE UNION – PTFE SEAT – EPDM SEALS – PLAIN ENDS



NEW VALVE HANDLE DESIGN GRADUALLY BEING INTRODUCED

d	PART NO	L	Z	H	A	B	C	E	F	PN	Wt (g)	Box
3/8"	021.82S1.01Q	14	44	72	50	10	58	39	21	15	100	60
1/2"	021.82S1.02Q	16	44	76	50	10	58	39	21	15	110	60
3/4"	021.82S1.03Q	19	52	90	60	11	65	47	24	15	170	90
1"	021.82S1.04Q	22	58	102	68	13	75	55	27	15	250	60
1 1/4"	021.82S1.05Q	26	66	118	80	18	75	60	30	15	370	35
1 1/2"	021.82S1.06Q	31	74	136	96	20	87	68	35	15	560	24
2"	021.82S1.07Q	38	92	168	116	20	101	80	40	15	980	12
2 1/2"	022.82S1.075Q	44	126	214	145	25	123	90	45	10	1825	5
3"	021.82S1.09Q	51	138	240	166	28	138	100	50	10	2900	3
4"	021.82S1.10Q	61	153	275	210	28	160	120	60	10	4790	2


STANDARD BALL VALVE – SINGLE UNION – PTFE SEAT – EPDM SEALS – THREADED ENDS



NEW VALVE HANDLE DESIGN GRADUALLY BEING INTRODUCED

G	PART NO	L	Z	H	A	B	C	E	F	PN	Wt (g)	Box
3/8"	021.82S3.01Q	14	44	72	50	10	58	39	21	15	100	60
1/2"	021.82S3.02Q	16	44	76	50	10	58	39	21	15	110	60
3/4"	021.82S3.03Q	19	52	90	60	11	65	47	24	15	170	90
1"	021.82S3.04Q	22	58	102	68	13	75	55	27	15	250	60
1 1/4"	021.82S3.05Q	26	66	118	80	18	75	60	30	15	370	35
1 1/2"	021.82S3.06Q	31	74	136	96	20	87	68	35	15	560	24
2"	021.82S3.07Q	38	92	168	116	20	101	80	40	15	980	12
2 1/2"	021.82S3.08Q	44	126	214	145	25	123	90	45	10	1825	5
3"	021.82S3.09Q	51	138	240	166	28	138	100	50	10	2900	3
4"	021.82S3.10Q	61	153	275	210	28	160	120	60	10	4790	2


STANDARD BALL VALVE – DOUBLE UNION – PTFE SEAT – EPDM SEALS – PLAIN ENDS



NEW VALVE HANDLE DESIGN GRADUALLY BEING INTRODUCED

d	PART NO	L	Z	H	A	B	C	E	F	PN	Wt (g)	Box
3/8"	021.66S1.01Q	14	53	81	50	10	58	39	21	15	140	60
1/2"	021.66S1.02Q	16	49	81	50	10	58	39	21	15	130	60
3/4"	021.66S1.03Q	19	56	94	60	11	65	47	24	15	200	36
1"	021.66S1.04Q	22	63	107	68	13	75	55	27	15	295	50
1 1/4"	021.66S1.05Q	26	72	124	80	18	75	60	30	15	440	30
1 1/2"	021.66S1.06Q	31	84	146	96	20	87	68	35	15	720	20
2"	021.66S1.07Q	38	94	170	116	20	101	80	40	15	1190	12
2 1/2"	022.66S1.075Q	44	130	218	145	25	123	90	45	10	2210	5
3"	021.66S1.09Q	51	148	250	166	28	138	100	50	10	3520	3
4"	021.66S1.10Q	61	168	290	210	28	160	120	60	10	5790	2

STANDARD BALL VALVE – DOUBLE UNION – PTFE SEAT – EPDM SEALS – THREADED ENDS



NEW VALVE HANDLE DESIGN GRADUALLY BEING INTRODUCED

G	PART NO	L	Z	H	A	B	C	E	F	PN	Wt (g)	Box
3/8"	021.66S3.01Q	14	53	81	50	10	58	39	21	15	140	60
1/2"	021.66S3.02Q	16	49	81	50	10	58	39	21	15	130	60
3/4"	021.66S3.03Q	19	56	94	60	11	65	47	21	15	200	36
1"	021.66S3.04Q	22	63	107	68	13	75	55	27	15	295	50
1 1/4"	021.66S3.05Q	26	72	124	80	18	75	60	30	15	440	30
1 1/2"	021.66S3.06Q	31	84	146	96	20	87	68	35	15	720	20
2"	021.66S3.07Q	38	94	170	116	20	101	80	40	15	1190	12
2 1/2"	021.66S3.08Q	44	130	218	145	25	123	90	45	10	2210	5
3"	021.66S3.09Q	51	148	250	166	28	138	100	50	10	3520	3
4"	021.66S3.10Q	61	168	290	210	28	160	120	60	10	5790	2

